



KF1JFL9

90° 弯美制 JIC 外螺纹 74° 外锥 / 轻系列法兰 ISO 6162-1
 90° ELBOW JIC MALE 74° CONE / L-SERIES FLANGE ISO 6162-1

代号 PART NO.	螺纹 THREAD		法兰型号 SIZE	O 形圈 O RING	尺寸 DIMENSIONS					
	E				A	B	b	D1	D2	S1
KF1JFL9-08	3/4"X16		1/2"	O210	32.5	44	6.73	30.2	24	19
KF1JFL9-08-12	3/4"X16		3/4"	O214	38	54.1	6.73	38.1	31.7	27
KF1JFL9-10-08	7/8"X14		1/2"	O210	37.5	44	6.73	30.2	24	22
KF1JFL9-10-12	7/8"X14		3/4"	O214	41	54.1	6.73	38.1	31.7	27
KF1JFL9-12	1.1/16"X12		3/4"	O214	44.5	54.1	6.73	38.1	31.7	27
KF1JFL9-12-16	1.1/16"X12		1"	O219	48	60.2	8	44.4	38	33
KF1JFL9-16	1.5/16"X12		1"	O219	49	60.2	8	44.4	38	33
KF1JFL9-16-12	1.5/16"X12		3/4"	O214	49	58	6.73	38.1	31.7	33
KF1JFL9-16-20	1.5/16"X12		1.1/4"	O222	54	66.5	8	50.8	43	41
KF1JFL9-20	1.5/8"X12		1.1/4"	O222	55.5	66.5	8	50.8	43	41
KF1JFL9-20-16	1.5/8"X12		1"	O219	55.5	65	8	44.4	38	41
KF1JFL9-20-24	1.5/8"X12		1.1/2"	O225	60	79.3	8	60.3	50	48
KF1JFL9-24	1.7/8"X12		1.1/2"	O225	62.5	79.3	8	60.3	50	48
KF1JFL9-24-20	1.7/8"X12		1.1/4"	O222	62.5	75.5	8	50.8	43	48
KF1JFL9-24-32	1.7/8"X12		2"	O228	74.5	108	9.53	71.4	62	63
KF1JFL9-32	2.1/2"X12		2"	O228	80	108	9.53	71.4	62	63

注：螺母及衬套需另行订货。管子直径 D 为公制时，配用螺母及衬套分别选用 NB200、NB500。
 管子直径为英制时，配用螺母及衬套分别选用 NB200、NB300。
 Note: Nut and sleeve should be ordered separately. The nut NB200 and sleeve NB500 is suitable for metric tube, the nut NB200 and sleeve NB300 is suitable for inch tube.