



KF20791

90° 国标公制内螺纹 74° 内锥面
90° GB METRIC FEMALE 74° CONE SEAT
参考 REF. GB/T 9065.1

代号 PART NO.	螺纹 E THREAD E	胶管 HOSE BORE		尺寸 DIMENSIONS			
		公称内径 DN	标号 DASH	A	C	H	S2
KF20791-12-04C	M12X1.25	6	04	30	9	33.5	17
KF20791-12-04	M12X1.5	6	04	30	10	33.5	17
KF20791-14-04	M14X1.5	6	04	30	8.5	34	19
KF20791-16-04	M16X1.5	6	04	30	8	35	22
KF20791-16-05	M16X1.5	8	05	34	8	38	22
KF20791-18-06	M18X1.5	10	06	35.3	10	41.3	24
KF20791-22-08	M22X1.5	12	08	41	10	48	27
KF20791-22-10	M22X1.5	16	10	56	10	52.5	27
KF20791-27-10	M27X1.5	16	10	56	11	54	32
KF20791-30-12	M30X1.5	20	12	66.2	11	63.5	36
KF20791-33-12	M33X2	20	12	65.5	13	63.5	41
KF20791-33-16	M33X2	25	16	76.7	13	69	41
KF20791-36-12	M36X2	20	12	65.5	14	63.5	41
KF20791-36-14	M36X2	22	14	71.2	14	64.5	41
KF20791-39-16	M39X2	25	16	76.7	14	70.5	46
KF20791-45-20W	M45X2	32	20	91.5	15	83	55
KF20791-52-20W	M52X2	32	20	93	17	84.5	60
KF20791-52-24W	M52X2	40	24	110.7	17	96.5	60

注：1. 表中代号用于编织软管。 2. 如需用于缠绕软管代号改为 20792-xx-xx。
Note: 1. For use with braided hoses. 2. If use with spiral hoses, hose fitting series number is 20792-xx-xx.