



KF24291



KF24291-T



KF24291W

90° 美制 ORFS 内螺纹平面
90° ORFS FEMALE FLAT SEAT
ISO 12151-1--SAE J516

代号 PART NO.	螺纹 E THREAD E	胶管 HOSE BORE		尺寸 DIMENSIONS			
		公称内径 DN	标号 DASH	A	H	C	S2
KF24291-04-04	9/16"X18	6	04	30	41	8.5	19
KF24291-04-05	9/16"X18	8	05	33	44	8.5	19
KF24291-06-05T	11/16"X16	8	05	33	37.5	10	22
KF24291-06-06	11/16"X16	10	06	35.3	49.3	10	22
KF24291-06-08	11/16"X16	12	08	41	55	10	22
KF24291-08-06T	13/16"X16	10	06	35.3	39.8	11	27
KF24291-08-08	13/16"X16	12	08	41	57.5	11	27
KF24291-08-10	13/16"X16	16	10	56.5	61.5	11	27
KF24291-10-08T	1"X14	12	08	41	46	13.5	30
KF24291-10-10	1"X14	16	10	56	66	13.5	30
KF24291-10-12	1"X14	20	12	65.5	75.5	13.5	30
KF24291-12-10T	1.3/16"X12	16	10	56	51.5	15	36
KF24291-12-12	1.3/16"X12	20	12	65.5	77	15	36
KF24291-12-16	1.3/16"X12	25	16	76.7	83.5	15	36
KF24291-16-12T	1.7/16"X12	20	12	65.5	63	14.8	41
KF24291-16-14T	1.7/16"X12	22	14	71.2	63	14.8	41
KF24291-16-16T	1.7/16"X12	25	16	76.9	67.5	14.8	41
KF24291-20-16T	1.11/16"X12	25	16	76.7	67.5	15	50
KF24291-20-20W	1.11/16"X12	32	20	93	100	15	50
KF24291-24-20T	2"X12	32	20	91.5	78.5	14.8	60
KF24291-24-24T	2"X12	40	24	109.4	92	14.8	60

注：1. 表中代号用于编织软管。 2. 如需用于缠绕软管代号改为 24292-xx-xx。
Note: 1.For use with braided hoses. 2.If use with spiral hoses, hose fitting series number is 24292-xx-xx.