



KF5B

英管外螺纹 60° 内锥或六角端面用
 组合垫密封 / 英管内螺纹 ISO 1179
 BSP MALE DOUBLE USE FOR 60° CONE SEAT
 OR BONDED SEAL / BSP FEMALE ISO 1179

代号 PART NO.	螺纹 THREAD		尺寸 DIMENSIONS				
	E	F	A	L	S1		
KF5B-02-04	G1/8"X28	G1/4"X19	11	29	19		
KF5B-04-02	G1/4"X19	G 1/8"X28	12	28	19		
KF5B-04	G1/4"X19	G1/4"X19	12	33	19		
KF5B-04-06	G1/4"X19	G3/8"X19	12	36	22		
KF5B-06-04	G3/8"X19	G1/4"X19	13.5	33.5	22		
KF5B-06	G3/8"X19	G3/8"X19	13.5	37.5	22		
KF5B-06-08	G3/8"X19	G1/2"X14	13.5	42.5	27		
KF5B-08-06	G1/2"X14	G3/8"X19	16	38	27		
KF5B-08	G1/2"X14	G1/2"X14	16	45	27		
KF5B-08-10	G1/2"X14	G5/8"X14	16	46	30		
KF5B-08-12	G1/2"X14	G3/4"X14	16	44.5	36		
KF5B-10-08	G5/8"X14	G1/2"X14	16	41.5	30		
KF5B-12-08	G3/4"X14	G1/2"X14	18.5	44.5	32		
KF5B-12	G3/4"X14	G3/4"X14	18.5	48	36		
KF5B-12-16	G3/4"X14	G1"X11	18.5	53.5	41		
KF5B-16-12	G1"X11	G3/4"X14	20.5	47.5	41		
KF5B-16	G1"X11	G1"X11	20.5	55.5	41		
KF5B-16-20	G1"X11	G1.1/4"X11	20.5	56.5	50		
KF5B-20-16	G1.1/4"X11	G1"X11	20.5	49	50		
KF5B-20	G1.1/4"X11	G1.1/4"X11	20.5	52.5	50		
KF5B-20-24	G1.1/4"X11	G1.1/2"X11	20.5	57.5	55		
KF5B-24	G1.1/2"X11	G1.1/2"X11	23	58	55		
KF5B-32-24	G2"X11	G1.1/2"X11	26	59.5	70		
KF5B-32	G2"X11	G2"X11	26	63	70		