



**KF1EH**

公制外螺纹 O 形圈平面密封 / 公制外螺纹 ISO 6149-2  
METRIC MALE O-RING/ METIRC MALE ISO 6149-2

代号 PART NO.	螺 纹 THREAD		O 形圈 O-RING		尺 寸 DIMENSIONS				
	E	F	E 端	F 端	A	B	L	S1	
KF1EH-12-10	M12X1.25	M10X1	8X1.9	O08.1X1.6	11	8.5	26.5	14	
KF1EH-14-12	M14X1.5	M12X1.5	10X1.9	O09.3X2.4	11	11	29.5	17	
KF1EH-16-14	M16X1.5	M14X1.5	11X1.9	O11.3X2.4	11	11	29.5	19	
KF1EH-18-16	M18X1.5	M16X1.5	13X1.9	O13.3X2.4	11	11.5	31.5	22	
KF1EH-22-18	M22X1.5	M18X1.5	16X2.4	O15.3X2.4	12	12.5	34.5	24	
KF1EH-27-22	M27X1.5	M22X1.5	20X2.4	O19.3X2.4	13	15	38	30	
KF1EH-30-27	M30X1.5	M27X2	24X2.4	O23.5X3.0	14	18.5	43.5	32	
KF1EH-36-33	M36X2	M33X2	30X3.1	O29.2X3.0	16	18.5	47.5	41	
KF1EH-39-33	M39X2	M33X2	32X3.1	O29.2X3.0	18	18.5	49.5	41	
KF1EH-42	M42X2	M42X2	35X3.1	O38.5X3.0	20	19	54	50	
KF1EH-45-42	M45X2	M42X2	38X3.1	O38.5X3.0	20	19	54	50	
KF1EH-52-48	M52X2	M48X2	40X3.1	O44.5X3.0	22	21.5	58.5	55	

注：1 E 端 O 形圈参数为外径与线径。 2 F 端与 ISO 9974-1 油口相配，去掉挡圈与 ISO 6149-1 油口相配。  
Note:1 The parameters of E end O-Ring are ring outside diameter and ring width.  
2 F end is connected with ISO 9974-1 port and connected with ISO 6149-1 port without retaining ring.