


**KF1QH9-OG**



**KF1QH9-OG/RN**

90° 弯公制 74° 外锥 / 公制外螺纹  
 可调向柱端轻系列 ISO 6149-3  
 90° ELBOW METRIC 74° CONE / METIRC MALE  
 ADJUSTABLE STUD END L-SERIES ISO 6149-3

代号 PART NO.	螺纹 THREAD		管子外径 D TUBE O.D.	O形圈 O-RING F 端	尺寸 DIMENSIONS				
	E	F			A	B	S1	S2	S3
KF1QH9-14-12OG	M14X1.5	M12X1.5	8	O09.3X2.4	30.2	32	14	17	17
KF1QH9-16-14OG	M16X1.5	M14X1.5	10	O11.3X2.4	32	35.5	16	19	19
KF1QH9-18-16OG	M18x1.5	M16x1.5	12	O13.3X2.4	34	36	19	22	22
KF1QH9-22-18OG	M22x1.5	M18x1.5	14	O15.3X2.4	37.5	39.5	22	24	27
KF1QH9-27-22OG	M27x1.5	M22x1.5	18	O19.3X2.4	41.5	43.5	27	27	32
KF1QH9-30-27OG	M30x1.5	M27x2	20	O23.5X3.0	45.8	50	30	32	36
KF1QH9-33-27OG	M33x2	M27x2	22	O23.5X3.0	49.5	52	33	32	41
KF1QH9-36-33OG	M36x2	M33x2	25	O29.2X3.0	51.5	54	36	41	41
KF1QH9-39-33OG	M39x2	M33x2	28	O29.2X3.0	55.5	57.2	41	41	46
KF1QH9-45-42OG	M45x2	M42x2	34	O38.5X3.0	62.5	61	48	50	50

注：1 如需带衬套及螺母整套订货，则请在代号后加“RN”，如 1QH9-22-18/RN，衬套代号 NB500-Q，螺母代号 NB200-Q。 2 F 端与 ISO 9974-1 油口相配，去掉挡圈则与 ISO 6149-1 油口相配。

Note: 1 In case if you are interested to order the adapter in complete set with sleeve and nut , it is necessary to insert suffix "RN" after our part no.,for example 1QH9-22-18/RN, The sleeve NO. is NB500-Q and the nut NO. is NB200-Q. 2 Fend is connected with ISO 9974-1 port and connected with ISO 6149-1 port without retaining ring.