



KF1BH

英管外螺纹60° 内锥或六角端面用组合垫密封/
公制外螺纹轻系列ISO 6149-3
BSP MALE DOUBLE USE FOR 60° CONE SEAT OR BONDED SEAL /
METRIC MALE L-SERIES ISO 6149-3

代号 PART NO.	螺纹 THREAD		O形圈 O-RING	尺寸 DIMENSIONS				
	E	F	F端	A	B	S1	L	
KF1BH-02-10	G1/8"X28	M10X1	O08.1X1.6	10	8.5	14	25	
KF1BH-02-12	G1/8"X28	M12X1.5	O09.3X2.4	10	11	17	28	
KF1BH-04-12	G1/4"X19	M12X1.5	O09.3X2.4	12	11	19	30	
KF1BH-04-14	G1/4"X19	M14X1.5	O11.3X2.4	12	11	19	31.5	
KF1BH-04-16	G1/4"X19	M16X1.5	O13.3X2.4	12	11.5	22	31.5	
KF1BH-06-14	G3/8"X19	M14X1.5	O11.3X2.4	13.5	11	22	35	
KF1BH-06-16	G3/8"X19	M16X1.5	O13.3X2.4	13.5	11.5	22	33	
KF1BH-06-18	G3/8"X19	M18X1.5	O15.3X2.4	13.5	12.5	24	36.5	
KF1BH-08-18	G1/2"X14	M18X1.5	O15.3X2.4	16	12.5	27	41	
KF1BH-08-22	G1/2"X14	M22X1.5	O19.3X2.4	16	13	27	41.5	
KF1BH-10-22	G5/8"X14	M22X1.5	O19.3X2.4	17.5	13	30	43	
KF1BH-12-16	G3/4"X14	M16X1.5	O13.3X2.4	18.5	11.5	32	43.5	
KF1BH-12-22	G3/4"X14	M22X1.5	O19.3X2.4	18.5	13	32	45	
KF1BH-12-27	G3/4"X14	M27X2	O23.5X3.0	18.5	16	32	45.5	
KF1BH-16-27	G1"X11	M27X2	O23.5X3.0	20.5	16	41	49	
KF1BH-16-33	G1"X11	M33X2	O29.5X3.0	20.5	16	41	49.5	
KF1BH-20-42	G1.1/4"X11	M42X2	O38.5X3.0	20.5	16	50	51.5	
KF1BH-24-48	G1.1/2"X11	M48X2	O44.5X3.0	23	17.5	55	55.5	

注：可与ISO 9974-1油口相配，去掉挡圈与ISO 6149-1油口相配。Note: fit for ISO 9974-1 port or ISO 6149-1 port when useless of retaining ring.