



美制螺纹O形圈密封柱端
UN、UNF THREAD STUD ENDS
WITH O-RING SEALING

KF1CO
KF1DO

KF1CO-RN
KF1DO-RN

代号 PART NO.	螺 纹 THREAD		管子外径 TUBE O.D.		尺 寸 DIMENSIONS						压力等级 MPa
	E	F	D1		B	l1	L1	S1	S2		
KF1CO-14-04	M14X1.5	7/16"X20	8		9	10	25	17	17	31.5 轻系列 L	
KF1CO-16-04	M16X1.5	7/16"X20	10		9	11	26	17	19		
KF1CO-18-06	M18X1.5	9/16"X18	12		10	11	26	19	22		
KF1CO-18-08	M18X1.5	3/4"X16	12		11	13	28	24	22		
KF1CO-18-10	M18X1.5	7/8"X14	12		12.7	14.3	29	27	22		
KF1CO-22-08	M22X1.5	3/4"X16	15		11	14	29	24	27		
KF1CO-22-10	M22X1.5	7/8"X14	15		12.7	15.3	30	27	27		
KF1CO-22-12	M22X1.5	1.1/16"X12	15		15.09	11.91	30	32	27		
KF1CO-26-08	M26X1.5	3/4"X16	18		11	14.5	31	27	32		
KF1CO-26-10	M26X1.5	7/8"X14	18		12.7	14.8	31	27	32		
KF1CO-30-08	M30X2	3/4"X16	18		11.13	13.87	33	32	36		
KF1CO-30-10	M30X2	7/8"X14	22		12.7	16.8	33	32	36		
KF1CO-30-12	M30X2	1.1/16"X12	22		15	16.5	33	32	36		
KF1CO-30-16	M30X2	1.5/16"X12	22		15	17.5	34	41	36		
KF1CO-36-12	M36X2	1.1/16"X12	28		15.09	14.41	34	41	41		
KF1CO-36-16	M36X2	1.5/16"X12	28		15	17.5	34	41	41		
KF1CO-45-16	M45X2	1.5/16"X12	35		15	17.5	39	46	50		
KF1CO-45-20	M45X2	1.5/8"X12	35		15.09	16.41	39	50	50		
KF1CO-52-20	M52X2	1.5/8"X12	42		15.09	15.91	42	55	60		
KF1DO-16-04	M16X1.5	7/16"X20	8		9	15	30	17	19	63 重系列 S	
KF1DO-18-06	M18X1.5	9/16"X18	10		10	14.5	31	19	22		
KF1DO-20-06	M20X1.5	9/16"X18	12		10	14.5	31	22	24		
KF1DO-20-08	M20X1.5	3/4"X16	12		11	17.5	34	24	24		
KF1DO-24-08	M24X1.5	3/4"X16	16		11	15.5	34	24	30		
KF1DO-24-10	M24X1.5	7/8"X14	16		12.7	18.8	37	27	30		
KF1DO-30-08	M30X2	3/4"X16	20		11	20.5	42	32	36		
KF1DO-30-10	M30X2	7/8"X14	20		12.7	20.8	42	32	36		
KF1DO-30-12	M30X2	1.1/16"X12	20		15	20.5	42	32	36		
KF1DO-36-12	M36X2	1.1/16"X12	25		15.09	19.91	47	41	46		
KF1DO-36-16	M36X2	1.5/16"X12	25		15	23	47	41	46		
KF1DO-42-16	M42X2	1.5/16"X12	30		15	23.5	50	46	50		
KF1DO-42-20	M42X2	1.5/8"X12	30		15	23.5	50	50	50		
KF1DO-52-20	M52X2	1.5/8"X12	38		15.09	22.9	53.9	55	60	31.5重系列S	

注：如需带卡套及卡套螺母整套订货，则请在代号后加“RN”，如1C9-30RN。
Note: In case if you are interested to order the adapter in complete set with cutting ring and nut ,it is necessary to insert suffix "RN" after our part no. , for example 1C9-30RN.