


KF20591



KF20591-T

90° 公制内螺纹24° 锥带O形圈重系列
90° METRIC FEMALE 24° CONE O-RING H.T.
ISO 12151-2—DIN 3865

代号 PART NO.	螺纹 E THREAD E	胶管 HOSE BORE		管子外径 TUBE O.D.	O 形圈 O RING	尺寸 DIMENSIONS			
		公称内径 DN	标号 DASH			A	C	H	S2
KF20591-14-04	M16X1.5	6	04	6	O04.5X1.5	30	1.5	39.5	19
KF20591-16-04	M16X1.5	6	04	8	O06.5X1.5	30	1.5	39.5	22
KF20591-16-05	M16X1.5	8	05	8	O06.5X1.5	33	1.5	42.5	22
KF20591-18-05T	M18X1.5	8	05	10	O08.0X1.5	33	1.5	41.5	22
KF20591-18-06	M18X1.5	10	06	10	O08.0X1.5	35.3	2	45.8	24
KF20591-20-06T	M20X1.5	10	06	12	O10.0X1.5	35.3	2.5	44.3	24
KF20591-20-08	M20X1.5	12	08	12	O10.0X1.5	41	2.5	61	27
KF20591-22-06T	M22X1.5	10	06	14	O11.0X2.0	35.3	3	44.8	27
KF20591-22-08	M22X1.5	12	08	14	O11.0X2.0	41	2.5	53	27
KF20591-24-08T	M24X1.5	12	08	16	O13.0X2.0	41	3	50.5	30
KF20591-24-10	M24X1.5	16	10	16	O13.0X2.0	56.5	2.5	56.5	30
KF20591-30-10T	M30X2	16	10	20	O16.3X2.4	56	2.5	58	36
KF20591-30-12	M30X2	20	12	20	O16.3X2.4	64.9	3	64	36
KF20591-36-12T	M36X2	20	12	25	O20.3X2.4	66.2	3.2	67.8	46
KF20591-36-14T	M36X2	22	14	25	O20.3X2.4	71.2	3.2	68.8	46
KF20591-42-16T	M42X2	25	16	30	O25.3X2.4	78	3.9	75.1	50
KF20591-52-20T	M52X2	32	20	38	O33.3X2.4	93	4.5	86.5	60
KF20591-52-24T	M52X2	40	24	38	O33.3X2.4	109.4	4.5	100	60

注：1. 表中代号用于编织软管。

2. 如需用于缠绕软管代号改为 20592-xx-xx。

Note: 1. For use with braided hoses.

2. If use with spiral hoses, hose fitting series number is 20592-xx-xx.